Docket No.: 66124-0002

Application No.: 10/700,174

Claims

What is claimed is:

- 1. (Withdrawn) A handheld assembly tool system for assembling fluid transfer lines that include a fitting and a tube, comprising:
- a fitting fixture for holding the fitting, the fitting fixture including a flange for supporting the fitting and a selectively adjustable retaining member configured to secure the fitting to the fitting fixture;
 - a tube fixture configured to hold the tube; and
- a press device selectively operable to engage and move the fitting fixture such that a portion of the fitting is forced into the tube.
- 2. (Withdrawn) The system of Claim 1, further including a first fastener for adjusting the position of the retaining member relative to the flange.
- 3. (Withdrawn) The system of Claim 1, wherein the fitting fixture includes a receptacle for securing the fitting fixture to the press device.
- 4. (Withdrawn) The system of Claim 3, wherein the receptacle is configured to receive a second fastener to secure the fitting fixture to the press device.
- 5. (Withdrawn) The system of Claim 1, wherein the press device includes a mechanically actuated ram, the fitting fixture secured to the ram for movement therewith.
- 6. (Currently Amended) A fitting fixture for use with a handheld assembly tool to assemble fluid transfer lines that include a fitting and a tube, comprising:
 - a body having first and second opposing planar surfaces;
- a flange for supporting the fitting, said flange extending outwardly from said first planar surface of said body;
 - a selectively adjustable retaining member for securing the fitting against the flange; and
- a receptacle for securing the fitting fixture to the assembly tool, said receptacle extending outwardly from said second planar surface; and

Application No.: 10/700,174

10/18/2005 15:40

Docket No.: 66124-0002

a hole formed through said body and in alignment with said receptacle.

- (Original) The fitting fixture of Claim 6, further including a guide member for 7. guiding movement of the fitting fixture relative to the assembly tool.
- (Withdrawn) A handheld assembly tool system for assembling fluid transfer 8. lines that include a fitting and a tube, comprising:
 - a press device including a moveable ram and a support cage;
- a fitting fixture for holding the fitting, the fitting fixture including a flange for supporting the fitting, a selectively adjustable retaining block for securing the fitting against the flange and a receptacle for securing the fitting fixture to the movable ram;
 - a tube fixture configured to hold the fluid conduit; and
- whereby the ram selectively operable to move the fitting fixture within the support cage such that a portion of the fitting is forced into the tube.
- 9. (Withdrawn) The system of Claim 8, further including a first fastener for adjusting the position of the retaining block relative to the flange.
- 10. (Withdrawn) The system of Claim 8, wherein the receptacle is configured to receive a second fastener to secure the fitting fixture to the press device.
- (Withdrawn) The system of Claim 8, where the fitting fixture further includes a 11. guide member for guiding movement of the fitting fixture within the support cage.
- (Withdrawn) The system of Claim 8, wherein the movable ram is positioned to 12. provide a reactive force along substantially parallel longitudinal axes of the fitting and the tube.
- (Withdrawn) The system of Claim 8, wherein the movable ram is configured to 13. engage the fitting.